

ON-BOARD DC-DC CONVERTER ENCAPSULATED MODULES 10 WATTS SINGLE & DUAL OUTPUT APS11DM-S & APS11DM-D SERIES



FEATURES:

- VERY LOW PROFILE 7 MM HIGH
- SINGLE & DUAL OUTPUT
- WIDE 4:1 INPUT RANGE
- 10W ISOLATED OUTPUT
- SIX-SIDED METAL SHIELD

SPECIFICATION

INPUT SPECIFICATION

Input Range: Wide 4:1 DC input range
See Ratings Chart

Input Voltage: Nominal 12/24/48Vdc

Input Current: Various with input range and load
See Ratings Chart

Input Fuse: Use external fuse

Input Filter: Pi-Network

Undervoltage Shutdown: 8Vdc

Isolation Resistor: 1,000 Mega Ohms

Isolation Voltage: 1,500Vdc

EMI: Six-sided metal shielding

Remote On/Off: TTL/CMOS-Compatible Input Control
Logic input reference to -input/-Vin
Logic [1]/Open(or 2.5-7.0Vdc above -Vin)=ON
Logic [2]/Short(or 0-0.08Vdc above -Vin)=OFF

OUTPUT SPECIFICATION

Output Voltage: See Ratings Chart

Output Current: See Ratings Chart

Voltage Accuracy: Main O/P $\pm 2.0\%$ typ.

Line Regulation: $\pm 0.5\%$ typ.

Load Regulation: Single O/P $\pm 1.0\%$ typ.
Dual O/P $\pm 2.0\%$ typ.

Noise & Ripple: Typ. 100mV for 3.3V/5.0V &
1.0% for others peak to peak

OVP: Built-in on main output

Adjustability: Not available

Short Circuit Protection: Power fold back,
Self-recovering

Overload Protection: About 130% of overrange by
foldback type

GENERAL SPECIFICATION

Efficiency: Typ. 78% various with input

Switching Frequency: Fixed frequency 450KHz

Circuit Topology: 450K Hz. Forward Circuit

Transient Response: Full to 1/2 load <200 μ Sec

Case: Black coated aluminum with non-conductive
metal base

Weight: 20.0g (0.71 Oz.)

Power Density: 17.2Watts./ Cubic inch

Operating Temperature: -40°C to +85°C range. -25°C to
+71°C @ full load without derating. Derating linearly
3.5%/ °C from +71°C @ full load to +85°C @ half-load

Storage Temperature: -55°C to +110°C

Humidity: Up to 95% RH, Non-condensing

Temperature Coefficient: 0.02% /°C

Cooling: Convection cooling up to 60°C @F-L. At least
100LFM moving air is recommended for F-L >+60°C in
a confined area

Commercial Grade: Full load up to +71°C with moving air

Industrial Grade: +71 to +85°C F-L to H-L with moving air

NOTE:(1) All measurements are at nominal input, full load and +25°C unless otherwise specified.

(2) Line Regulation measured from High to Low Lines at full load.

(3) Load Regulation measured from Full Load (F-L) to Half-Load (H-L) at nominal input.

(4) Correct fuse size by calculating the max. DC current drain at low Line input & Load and then adding 20-25% for the desired fuse size.

