

ZKS-150N80

PS-III

150W Six-Output PC Power Supply

150Watts



STANDARD FEATURES

- 3.3V Output
- +5VSB standby
- ATX 20-pin connector
- Remote On/Off
- Energy Star
- High efficiency
- High MTBF
- IEC1000-2, -4, -5
- Power good signal
- CE MARK

SAFETY

- UL/CUL 1950
- TUV 60950
- CB (IEC 950)
- NEMKO 60950

EMI/RFI

- FCC Class B
- CISPR 22 Class B

OPTIONAL FEATURES

- AC outlet or AC switch
- Thermal fan speed control
- Fan monitor & fan control

ELECTRICAL SPECIFICATION

Input

Input range.....	95~130 / 189~260 VAC; Switch select
Frequency.....	47~63 Hz
Input current.....	4.3A @ 115VAC; 2.2A @ 230VAC
Inrush current.....	< 50A @ 115VAC at 25°C < 100A @ 230VAC at 25°C
Efficiency.....	> 60% full load at 115VAC

Output

Total maximum power.....	150 watts continuous
Transient response.....	All output shall stay within regulation for 20% load change from 10Hz to 1KHz and 50% duty cycle

Over current protection.....	< 240VA
Over voltage protection.....	+3.3V trip point < 4.8V +5V trip point < 7.5V +12V trip point < 16.5V

Short-circuit protection..... Main outputs latch off when short-circuits to common or other outputs

Timing Sequence

Power good signal.....	100 ~500ms turn-on delay time > 1ms before power fail
Hold-up time.....	>10ms at full load at 115Vac/60Hz

Remote On-Off

PS-on.....	TTL compatible; active low enables main outputs
------------	---

MECHANICAL / ENVIRONMENTAL

Dimension.....	150 x 100 x 86 (mm) LxWxH
Cooling.....	80mm sleeve bearing fan
Operating temp. / humidity.....	10 ~ 40°C / 20 ~ 85%
Storage temp. / humidity.....	-10 ~ 70°C / 10 ~ 95%
MTBF.....	50,000 hours at full load 25°C (MIL-217-F)

with AC inlet and power switch

Output	Voltage	Regulation	Minimum Load	Maximum Load	Peak Load ¹	Ripple P/P (PARD) ²	Ripple & Noise ²
V1 ³	+3.3	+/- 5%	0.2A	8A	12A	60mV	90mV
V2	+5	+/- 5%	2.5A	15A	18A	70mV	100mV
V3	+12	+/- 6%	0.7A	3.2A	5A	150mV	180mV
V4	-5	+/- 5%	0A	0.3A	0.5A	150mV	200mV
V5	-12	+/- 10%	0.05A	0.3A	0.5A	150mV	200mV
V6	+5VSB	+/- 5%	0.05A	1.5A	1.5A	100mV	100mV

1. Limited to 12 second maximum.

2. Peak-to-peak value; 20MHz bandwidth; Measured with 10 μF and 0.1 μF tantalum capacitors in parallel to load.

3. Total maximum combined output power on +3.3V and +5V rail is 100 watts