

## 1. PACKAGE OUTLINE TABLE

	Suffix	3Pin	4Pin	5Pin	6Pin	8Pin	10Pin	14Pin	16Pin	18Pin	20Pin	22Pin
TO-92	L*1	√	—	—	—	—	—	—	—	—	—	—
TO-220F	F	√	*√	—	—	—	—	—	—	—	—	—
TO-220	T*2	—	—	√	—	—	—	—	—	—	—	—
TO-252	DL	√	—	—	—	—	—	—	—	—	—	—
SOT-89	U	√	—	√	—	—	—	—	—	—	—	—
MTP	F	—	—	√	√	—	—	—	—	—	—	—
SC-88A	F	—	—	√	—	—	—	—	—	—	—	—
DIP	D/N	—	—	—	—	√	—	√	√	√	√	√
SDIP	L	—	—	—	—	—	—	—	—	—	—	√
DMP	M	—	—	—	—	√	—	√	√	—	√*3	—
SOP	G	—	—	—	—	√	—	—	—	√	√	√
EMP	E	—	—	—	—	√	—	√	√	—	√	—
SSOP	V	—	—	—	—	√	√	√	√	—	√	—
VSP	R	—	—	—	—	√	√	—	—	—	—	—
FLP	K	—	—	—	√	—	√	—	—	—	—	—
SIP	S/L	—	—	—	—	√	—	—	—	—	—	—
ZIP	S	—	—	—	—	—	—	—	—	√	—	—
FFP	P	—	—	—	—	—	—	—	√	—	—	—

	Suffix	24Pin	28Pin	30Pin	32Pin	40Pin	42Pin	44Pin	56Pin	64Pin	80Pin	100Pin
DIP	D/N	√*4	—	—	—	√	—	—	—	—	—	—
SDIP	L	√	√	√	—	—	√	—	√	—	—	—
DMP	M	√	—	√*5	—	—	√	—	—	—	—	—
SOP	G	√*4	√	—	—	√	—	—	—	—	—	—
EMP	E	√	—	—	—	—	—	—	—	—	—	—
SSOP	V	√	—	—	—	—	—	—	—	—	—	—
PLCC	F	—	√	—	—	—	—	—	—	—	—	—
QFP	F	—	—	—	*√	—	—	√	√	√	√	√
FFP	P	√	—	—	√	—	—	—	—	—	—	—

\*Under Development

\*1 Except NJM78L, NJM79L series

\*2 Suffix "T" is applied to only TO-220(5pin) package.

\*3 Lead pitch : 0.95mm.

\*4 DIP24 and SOP24 are applied to only NJU9702. DIP24-D2 is applied to only Motor Driver IC.

\*5 Lead pitch : 1.0mm(SDMP30)

