



Main no. 800.962.0380  
 Fax no. 860.295.0670

[Request for Quote](#)

[Local Sales Offices Nationwide](#)

**Shicoh Engineering**  
**Axial Flow 30mm TYPE: 30mm x 30mm**

[Return to Table of Contents](#)  
[Return to General Specifications](#)

[Return](#)

Contact Pik Power for more information.

<b>F3010CG</b> Type		Oil circulate bearing	30*30*10.2mm		
Model	F3010CG-05RCV	F3010VG-12PCV			
Rated Voltage (DCV)	5	12			
Operating Voltage Range (DCV)	4.5~5.5	10.2~13.8			
Rated Current (A)	0.18	0.08			
Rated Input (W)	0.9	0.98			
Max Air Volume (m <sup>3</sup> /min)	0.064	0.055			
Max Static Pressure (Pa)	15.4	10			
A-weighted Noise Level (dB)	19 (1m)	22 (1m)			
Rotational Freq. (min <sup>-1</sup> )	5,400	4,500			
Life expectancy (Hour)	20,000 (Room temperature/humidity)				

Catalogs are in Adobe's PDF (portable document file), a cross platform format. Files are viewed with Adobe's Acrobat Reader. If you need the free reader, [click here](#).

PIK Power represented by: Precision Sales & Associates

Created & maintained by [og-images](#).