



Main no. 800.962.0380  
 Fax no. 860 295.0670

[Request for Quote](#)

[Local Sales Offices Nationwide](#)

**Shicoh Engineering**  
**Axial Flow 60mm TYPE: 60mm x 60mm**

[Return to Table of Contents](#)  
[Return to General Specifications](#)

[Return](#)

Contact Pik Power for more information.

<b>F6020AP</b> Type	Ball Bearing		60 x 60 x 20mm		
<b>Model</b>	F6020AP-05MCW 0620-5	F6020AP-12KCW 0620-12LL	F6020AP-12LCW 0620-12L	F6020AP-12PCW 0620-12	F6020AP-24PCW 0620-24
Rated Voltage (DCV)	5	12	12	12	24
Operating Voltage Range (DCV)	4.5~5.5	10.2~13.8	10.2~13.8	10.2~13.8	20.4~27.6
Rated Current (A)	0.3	0.08	0.1	0.2	0.1
Rated Input (W)	1.5	0.96	1.2	2.4	2.4
Max Air Volume (m <sup>3</sup> /min) / (cfm)	0.3 / 10.6	0.2 / 7.1	0.3 / 10.6	0.35 / 12.4	0.35 / 12.4
Max Static Pressure (Pa)	17.6	8.8	19.6	29.4	29.4
A-weighted Noise Level (dB)	28 (1m)	25 (1m)	28 (1m)	33 (1m)	33 (1m)
Rotational Freq. (min <sup>-1</sup> )	3,500	2,700	3,200	4,500	4,500
Life expectancy (Hour)	50,000 (Room temperature/humidity)				

Catalogs are in Adobe's PDF (portable document file), a cross platform format. Files are viewed with Adobe's Acrobat Reader. If you need the free reader, click [here](#).