





Local Sales Offices Nationwide



Shicoh Engineering Axial Flow 80mm TYPE: 80mm x 80mm

Return to Table of Contents
Return to General Specifications



Contact Pik Power for more information.

<b>F8015AP</b> Type		1Ball 1Sleeve		80*80*15mm
4-04-3 ABEL 73.244 S(49)	PROFILE TO THE PROFIL		AJR FLUW	RJITATIJN
Model	F8015AP-12LCW	F8015AP-24LCW		
Rated Voltage (DCV)	12.0	24.0		
Operating Voltage Range (DCV)	10.2~13.8	20.4~27.6		
Rated Current (A)	0.2	0.1		
Rated Input (W)	2.4	2.4		
Max Air Volume (m <sup>3</sup> /min)	0.52	0.52		
Max Static Pressure (Pa)	2.8	2.8		
A-weighted Noise Level (dB)	32 (1m)	32 (1m)		
Rotational Freq. (min <sup>-1</sup> )	3,000	3,000		
Life expectancy (Hour)	50,000 (Room temperature/humidity)			

Catalogs are in Adobe's PDF (portable document file), a cross platform format. Files are viewed with Adobe's Acrobat Reader. If you need the free reader, click <a href="here">here</a>.

PIK Power represented by: Precision Sales & Associates

Created & maintained by og-images.

1 of 1 8/23/2013 3:09 PM