



DIN RAIL Series

40/60/100 Watt Single Output



Features

- * Universal Input Range 90-264VAC
- * Efficiency up to 90%
- * Meets EN55022 and CISPR/FCC Class B
- * Continuous Short Circuit Protection
- * LED Indicator for Power ON
- * Can be Installed on DIN rail TS-35/7.5 or 15



CFM40CXXX-DR Series

MODEL	OUTPUT VOLTAGE	MAX. LOAD	MIN. LOAD	RIPPLE & NOISE	VOLTAGE ACCURACY	LINE REGULATION	LOAD REGULATION	%EFF. (Typ.)
CFM40C033-DR	3.3V	6A	0A	50mV	±1%	±0.5%	±1%	70%
CFM40C050-DR	5V	6A	0A	1%	±1%	±0.5%	±1%	76%
CFM40C090-DR	9V	4.45A	0A	1%	±1%	±0.5%	±1%	84%
CFM40C120-DR	12V	3.34A	0A	1%	±1%	±0.5%	±1%	85%
CFM40C150-DR	15V	2.67A	0A	1%	±1%	±0.5%	±1%	85%
CFM40C240-DR	24V	1.67A	0A	1%	±1%	±0.5%	±1%	85%
CFM40C300-DR	30V	1.33A	0A	1%	±1%	±0.5%	±1%	86%
CFM40C360-DR	36V	1.11A	0A	1%	±1%	±0.5%	±1%	87%
CFM40C480-DR	48V	0.834A	0A	1%	±1%	±0.5%	±1%	87%

CFM60CXXX-DR Series

MODEL	OUTPUT VOLTAGE	MAX. LOAD	MIN. LOAD	RIPPLE & NOISE	VOLTAGE ACCURACY	LINE REGULATION	LOAD REGULATION	%EFF. (Typ.)
CFM60C033-DR	3.3V	8A	0A	50mV	±1%	±0.5%	±1%	72%
CFM60C050-DR	5V	8A	0A	1%	±1%	±0.5%	±1%	77%
CFM60C090-DR	9V	6.67A	0A	1%	±1%	±0.5%	±1%	84%
CFM60C120-DR	12V	5A	0A	1%	±1%	±0.5%	±1%	85%
CFM60C150-DR	15V	4A	0A	1%	±1%	±0.5%	±1%	86%
CFM60C240-DR	24V	2.5A	0A	1%	±1%	±0.5%	±1%	86%
CFM60C300-DR	30V	2A	0A	1%	±1%	±0.5%	±1%	86%
CFM60C360-DR	36V	1.67A	0A	1%	±1%	±0.5%	±1%	88%
CFM60C480-DR	48V	1.25A	0A	1%	±1%	±0.5%	±1%	88%

CFM101CXXX-DR Series

MODEL	OUTPUT VOLTAGE	MAX. LOAD	MIN. LOAD	RIPPLE & NOISE	VOLTAGE ACCURACY	LINE REGULATION	LOAD REGULATION	%EFF. (Typ.)	PF (Typ.)
CFM101C120-DR	12V	8.4A	0A	1%	±1%	±0.5%	±1%	87%	0.9
CFM101C150-DR	15V	6.7A	0A	1%	±1%	±0.5%	±1%	87%	0.9
CFM101C200-DR	20V	5A	0A	1%	±1%	±0.5%	±1%	88%	0.9
CFM101C240-DR	24V	4.2A	0A	1%	±1%	±0.5%	±1%	88%	0.9
CFM101C480-DR	48V	2.1A	0A	1%	±1%	±0.5%	±1%	90%	0.9

