



Main no. 800.962.0380  
 Fax no. 860.295.0670

[Request for Quote](#)

[Local Sales Offices Nationwide](#)

**Shicoh Engineering**  
**Axial Flow 25mm TYPE: 25mm x 25mm**

[Return to Table of Contents](#)  
[Return to General Specifications](#)

[Return](#)

Contact Pik Power for more information.

<b>F2510CT</b> Type		Oil circulate bearing	25*25*10mm		
<p>The drawing shows three views of the fan. The front view on the left is a square with dimensions 25±0.5 mm width and 20±0.3 mm height. It features a central hub with a 'LABEL' and three mounting holes with diameter 2.8±0.2 mm. The side view in the middle shows a height of 10±0.5 mm and a mounting hole offset of 125±1.0 mm. The rear view on the right shows the fan's rotation direction with an arrow labeled 'ROTATION'. A central arrow labeled 'AIR FLOW' points to the left.</p>					
<b>Model</b>	F2510CT-12UCV				
Rated Voltage (DCV)	12.0				
Operating Voltage Range (DCV)	10.2~13.8				
Rated Current (A)	0.04				
Rated Input (W)	0.48				
Max Air Volume (m <sup>3</sup> /min)	0.048				
Max Static Pressure (Pa)	18				
A-weighted Noise Level (dB)	22 (1m)				
Rotational Freq. (min <sup>-1</sup> )	7,500				
Life expectancy (Hour)	20,000 (Room temperature/humidity)				

Catalogs are in Adobe's PDF (portable document file), a cross platform format. Files are viewed with Adobe's Acrobat Reader. If you need the free reader, click [here](#).

PIK Power represented by: Precision Sales & Associates

Created & maintained by [og-images](#).