





Local Sales Offices Nationwide



Shicoh Engineering Axial Flow 30mm TYPE: 30mm x 30mm

Return to Table of Contents Return to General Specifications



Contact Pik Power for more information.

F3010AP Type		Ball Bearing		30 x 30 x 10.2mm
	4- \$\phi 3.2			
Model	F3010AP-05PCW (0310-5)	F3010AP-12RCW (0310-12)	F3010AP-12UCW (0310-12H)	
Rated Voltage (DCV)	5	12	12	
Operating Voltage Range (DCV)	4.5~5.5	10.2~13.8	10.2~13.8	
Rated Current (A)	0.11	0.095	0.19	
Rated Input (W)	0.55	1.14	2.28	
Max Air Volume (m ³ /min) / (cfm)	0.04 / 1.4	0.06 / 2.1	0.08 / 2.8	
Max Static Pressure (Pa)	6.86	12.3	23.0	
A-weighted Noise Level (dB)	25 (1m)	26 (1m)	30 (1m)	
Rotational Freq. (min ⁻¹)	4,400	5,600	8,300	
Life expectancy (Hour)	50,000 (Room temperature/humidity)			

Catalogs are in Adobe's PDF (portable document file), a cross platform format. Files are viewed with Adobe's Acrobat Reader. If you need the free reader, click here.

PIK Power represented by: Precision Sales & Associates

Created & maintained by og-images.

1 of 1