



Main no. 800.962.0380  
Fax no. 860.295.0670

[Request for Quote](#)

[Local Sales Offices Nationwide](#)

**Shicoh Engineering**  
**Axial Flow 60mm TYPE: 60mm x 60mm**

[Return to Table of Contents](#)  
[Return to General Specifications](#)

[Return](#)

Contact Pik Power for more information.

<b>F6010AP</b> Type	Ball Bearing		60 x 60 x 10.3mm			
Model	F6010AP-05LCW 0610-5	F6010AP-12KCW 0610-12L	F6010AP-12LCW 0610-12	F6010AP-12NCW 0610-12H	F6010AP-12PCW 0610-12HH	F6010AP-24MCW 0610-24
Rated Voltage (DCV)	5	12	12	12	12	24
Operating Voltage Range (DCV)	4.5~5.5	10.2~13.8	10.2~13.8	10.2~13.8	10.2~13.8	20.4~27.6
Rated Current (A)	0.18	0.08	0.1	0.13	0.15	0.08
Rated Input (W)	0.9	0.96	1.2	1.56	1.8	1.92
Max Air Volume (m <sup>3</sup> /min) / (cfm)	0.3 / 10.6	0.28 / 9.9	0.33 / 11.7	0.36 / 12.7	0.4 / 14.1	0.35 / 12.4
Max Static Pressure (Pa)	16.7	12.7	16.7	22.5	29.4	20.6
A-weighted Noise Level (dB)	28 (1m)	25 (1m)	30 (1m)	36 (1m)	38 (1m)	33 (1m)
Rotational Freq. (min <sup>-1</sup> )	3,200	2,800	3,300	3,800	4,200	3,500
Life expectancy (Hour)	50,000 (Room temperature/humidity)					

Catalogs are in Adobe's PDF (portable document file), a cross platform format. Files are viewed with Adobe's Acrobat Reader. If you need the free reader, click [here](#).

PIK Power represented by: Precision Sales & Associates

Created & maintained by [og-images](#).