



Main no. 800.962.0380
 Fax no. 860 295.0670

[Request for Quote](#)

[Local Sales Offices Nationwide](#)

Shicoh Engineering
Axial Flow 80mm TYPE: 80mm x 80mm

[Return to Table of Contents](#)
[Return to General Specifications](#)

[Return](#)

Contact Pik Power for more information.

F8020AP Type	1Ball 1Sleeve		80*80*20mm		
Model	F8020AP-12KCV	F8020AP-24KCV			
Rated Voltage (DCV)	12.0	24.0			
Operating Voltage Range (DCV)	10.2~13.8	20.4~27.6			
Rated Current (A)	0.22	0.12			
Rated Input (W)	2.64	2.88			
Max Air Volume (m ³ /min)	0.65	0.65			
Max Static Pressure (Pa)	2.4	2.4			
A-weighted Noise Level (dB)	30 (1m)	30 (1m)			
Rotational Freq. (min ⁻¹)	2,800	2,800			
Life expectancy (Hour)	50,000 (Room temperature/humidity)				

Catalogs are in Adobe's PDF (portable document file), a cross platform format. Files are viewed with Adobe's Acrobat Reader. If you need the free reader, click [here](#).

PIK Power represented by: Precision Sales & Associates

Created & maintained by og-images.